

TECHNICAL SPECIFICATION



Property	Test Method	Result
Dimensions	EN 427	1220*180mm
Thickness Over All	EN 428	3.0 mm, 4.0 mm, 5.0 mm, 7.0 mm
Thickness Wear Layer	EN 429	0.3 mm, 0.5 mm
Pell Strength of Layers	EN 431	Pass
Shear Forces of Layers	EN 432	Good
Residual Indentations	EN 433	Mean Value ≤ 0.1mm
Dimension Stability	EN 434	Shrinkage ≤ 0.12%/Curling ≤ 1.2mm
Resistance to Chemicals	EN 423	Class 0
Castot Chair Continuous	EN 425	No Disturbance/No Delamination
Light Fastness	ISO 105 B02	≥ 6
ASTM E84-03	NFPA Class B1	
Slip Resistance	DIN 51130	R9

Specification

SPC core thickness	4 to 6 MM
Wear layer	0.3 AND 0.5 MM
Plank Size	180 X 1220 MM AND 228.6 X 1219.2 MM AND 228.6 X 1524 MM
Padding	IXPE Black 1.00 AND 1.50 MM
Material	100 % Virgin
Click Lock	Unilin Uniclic
Warranty	25 Years Residential 10 Years Commercial

